



24V DIN Rail Mountable Power Supply

- Universal AC Input / Full Range
- Protections: Short Circuit / Overload / Over Voltage
- Cooling by Free Air Convection
- DIN Rail TS-35/7.5 or 15 Compatible
- LED Indicator for Power On



R33100
RoHS



TPTC004




BS EN/EN62368-1




Model	Part #	4010-0013
Output	DC Voltage	24V
	Rated Current	4A
	Current Range	0 ~ 4A
	Rated Power	96W
	Ripple & Noise (max) ²	150mVp-p
	Voltage Adj. Range	24 ~ 30V
	Voltage Tolerance ³	±1.0%
	Line Regulation	±1.0%
	Load Regulation	±1.0%
Input	Setup, Rise Time ⁵	3000ms, 50ms / 230VAC 3000ms, 50ms / 115VAC @ Full Load
	Hold Up Time (Typ.)	50ms/230VAC & 20ms/115VAC @ Full Load
	Voltage Range	85 ~ 264VAC / 120 ~ 370VDC
	Frequency Range	47 ~ 63Hz
	Efficiency (Typ.)	86%
	AC Current (Typ.)	1.3A / 115VAC 0.8A / 230VAC
Protection	Inrush Current (Typ.)	Cold Start 30A / 115VAC & 60A / 230VAC
	Leakage Current	<1mA / 240VAC
	Overload	105 ~ 150% rated output power Protection Type: Constant current limiting, recovers automatically after fault condition removed
Function	Over Voltage	31.2 ~ 36V Protection Type: Shut down o/p voltage, re-power on to recover
	DC OK Signal	Relay contact rating (max): 30V / 1A resistive
Environment	Working Temp.	-10 ~ 60°C
	Working Humidity	20 ~ 90% RH non-condensing
	Storage Temp., Humidity	-40 ~ 85°C, 10-95% RH
	Temp. Coefficient	±0.03%/°C (0 ~ 50°C)
Safety & EMC	Vibration	10 ~ 500Hz, 2G 10min. / 1 cycle, period for 60min. along X, Y, Z axis
	Certifications	CE UKCA, UL, EAC
	Withstand Voltage	I/P-O/P: 3KVAC, I/P-FG: 2KVAC, O/P-FG: 0.5KVAC
	Isolation Resistance	I/P-O/P, I/P-FG, O/P-FG: >100M Ohms / 500VDC / 25°C / 70% RH
Notes	Dimension (W*H*D)	2.17 x 3.54 x 3.94 inches [55 x 90 x 100 mm]
	<p>1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.</p> <p>2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1µF & 47µF parallel capacitor.</p> <p>3. Tolerance : includes set up tolerance, line regulation and load regulation.</p> <p>4. The power supply is considered a component which will be installed into a final equipment. The final equipment must be re-confirmed that it still meets EMC directives. For guidance on how to perform these EMC tests, please refer to "EMI testing of component power supplies"</p> <p>5. Length of set up time is measured at first cold start. Turning ON/OFF the power supply may lead to an increase of the set-up time.</p> <p>6. The ambient temperature derating of 3.5°C/1000m with fanless models and of 5°C/1000m with fan models for operating altitude higher than 2000m(6500ft).</p>	

4010-0013



TOP VIEW



SIDE VIEW

- A VDC Output
- B Power On Indicator LED
- C Voltage Adjustment Screw
- D VDC Input